

## \* ) TĒRAUDA CAURULE


El-metināta  
DIN 2458/1626  
3.1.B sertifikāts - V = 1,0



VVS nr.	mm	kg/m
02 2125.022	21,3x3,2	1,43
.029	26,9x3,2	1,87
.034	33,7x2,6	1,99
.036	33,7x4,05	2,93
.038	38,0x2,6	2,27
.042	42,4x2,6	2,57
.043	42,4x3,2	3,14
.046	42,4x4,5	4,21
.048	48,3x2,6	2,95
.053	48,3x4,5	4,86
.060	60,3x2,9	4,14
.064	60,3x4,5	6,19
.070	70,0x2,9	4,80
.076	76,1x2,9	5,28
.080	76,1x4,5	7,95
.089	88,9x3,2	6,81
.092	88,9x4,5	9,37
.093	88,9x5,0	10,30
.102	101,6x3,6	8,76
.107	108,0x3,2	8,27
.108	108,0x3,6	9,33
.114	114,3x3,6	9,99
.116	114,3x4,5	12,20
.118	144,3x5,6	15,00
.130	133,0x2,9	9,30
.132	133,0x3,6	11,50
.133	133,0x4,0	12,80
.137	139,7x2,9	9,78
.140	139,7x4,0	13,50
.141	139,7x4,5	15,00
.143	139,7x5,6	18,50
.156	159,0x2,9	11,20
.160	159,0x4,5	17,10
.168	168,3x4,5	18,10
.171	168,3x6,3	25,20
.194	193,7x5,6	26,00
.219	219,0x6,3	33,10
.273	273,0x6,3	41,60
.324	323,9x7,1	55,50
.406	406,4x8,8	86,30

## \* ) TĒRAUDA ATLOKS AR VĪTNI


DIN: 2566 - DS: 58  
Spiediens: 16 bar



VVS nr.	Collas
00 0581.004	1/2"
.006	3/4"
.008	1"
.010	1 1/4"
.011	1 1/2"
.012	2"
.013	2 1/2"
.014	3"
.016	4"

## \* ) CINKOTS TĒRAUDA ATLOKS AR VĪTNI


DIN: 2566 - DS: 581  
Spiediens: 16 bar



VVS nr.	Collas
00 0581.404	1/2"
.406	3/4"
.408	1"
.410	1 1/4"
.411	1 1/2"
.412	2"
.413	2 1/2"
.414	3"
.416	4"
.418	5"

## \* ) TĒRAUDA ATLOKS METINĀMS

DIN: 2576 B - DS: 601  
Spiediens: 10 bar



VVS nr.	mm
00 0601.027	26,9 mm
.034	33,7 mm
.038	38,0 mm
.042	42,4 mm
.048	48,3 mm
.060	60,3 mm
.076	76,1 mm
.089	88,9 mm
.108	108,0 mm
.114	114,3 mm
.133	133,0 mm
.140	139,7 mm
.159	159,0 mm
.168	168,3 mm
.194	193,7 mm
.219	219,1 mm
.273	273,0 mm
.324	323,9 mm
.406	406,4 mm