


## PERFORĒTAS LOKSNES




Izmērs: 2000x1000 mm

| Biezums<br>mm  | Acs<br>mm | «Caurā»<br>virsmā % | Att. centr.<br>mm | Kods    |
|--|-----------|---------------------|-------------------|---------|
| <b>Kvalitāte - ST. 12-03</b>                                       |           |                     |                   |         |
| 1,0  |           | 47,0                |                   | 0429548 |
| 2,0  |           | 47,0                |                   | 0900191 |
| <b>Cinkotas</b>  |           |                     |                   |         |
| 1,0  |           | 47,0                |                   | 0429555 |
| <b>Acs kvadrātveida - Kvalitāte ST. 12-03</b>                      |           |                     |                   |         |
| 1,0  | 9,5       | 50,8                | 13,33             | 1044106 |
| 1,0  | 10,0      | 69,4                | 12,00             | 0906768 |
| 1,5  | 9,0       | 7,0                 | 34,00             | 1042696 |
| 1,5  | 9,5       | 50,8                | 13,33             | 1044114 |
| 1,5  | 10,0      | 69,4                | 12,00             | 0900563 |
| 2,0  | 9,5       | 50,8                | 13,33             | 0682435 |
| <b>Acs apaļa - Kvalitāte ST. 12-03 / ST.37.2</b>                   |           |                     |                   |         |
| 1,0  | 2,0       | 29,6                | 3,50              | 1044122 |
| 1,0  | 3,0       | 32,6                | 5,00              | 0429571 |
| 1,0  | 4,0       | 46,2                | 5,60              | 1044130 |
| 1,0  | 5,0       | 40,3                | 7,50              | 0350264 |
| 1,5  | 3,0       | 32,6                | 5,00              | 1044148 |
| 1,5  | 4,0       | 46,2                | 6,00              | 0350223 |
| 1,5  | 5,0       | 40,3                | 5,00              | 1044155 |
| 1,5  | 10,0      | 56,2                | 12,70             | 1044163 |
| 2,0  | 2,0       | 29,6                | 3,50              | 1044171 |
| 2,0  | 3,0       | 32,6                | 5,00              | 1044189 |
| 2,0  | 5,0       | 35,4                | 8,00              | 1044197 |
| 2,0  | 8,0       | 47,9                | 11,00             | 0350470 |
| 2,0  | 10,0      | 56,2                | 12,70             | 1044205 |
| 3,0  | 3,0       | 32,6                | 4,00              | 1044213 |
| 3,0  | 10,0      | 40,3                | 15,00             | 0350520 |
| <b>Acs apaļa - Kvalitāte cinkota</b>                               |           |                     |                   |         |
| 1,0  | 3,0       | 32,6                | 5,00              | 1155001 |
| 1,0  | 5,0       | 40,3                | 7,50              | 1155019 |
| <b>Acs apaļa - Kvalitāte nerūs. tērauds AISI 304/W 4301</b>        |           |                     |                   |         |
| 1,0  | 2,0       | 29,6                | 3,00              | 0575860 |
| 1,0  | 4,0       | 46,2                | 5,60              | 0575878 |
| 1,5  | 5,0       | 40,3                | 7,50              | 0575886 |
| 1,5  | 10,0      | 56,2                | 12,70             | 0575894 |
| 2,0  | 5,0       | 35,4                | 8,00              | 0575936 |
| 2,0  | 8,0       | 47,9                | 11,00             | 0575944 |
| 2,0  | 10,0      | 56,2                | 12,70             | 0575951 |
| <b>Acs kvadrātveida - Kvalitāte nerūs. tērauds AISI 304/W 4301</b> |           |                     |                   |         |
| 1,0  | 9,5       | 50,8                | 13,33             | 0575993 |

## TĒRAUDA PROFILS


UNP - S 235 JRG2/EN 10025  
(Rst 37-2)  
Sertifikāts 2.2 (3.1.B)/EN 10204  
Tolerance DIN 1026  
Izmērus skat. 69 lpp.



| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 80x 6050 .....  | 0431346 | 8,6  |
| 80x12100 .....  | 0431353 | 8,6  |
| 100x 6050 ..... | 0431361 | 10,6 |
| 100x12100 ..... | 0431379 | 10,6 |
| 100x14100 ..... | 0974071 | 10,6 |
| 120x 6050 ..... | 0431387 | 13,4 |
| 120x12100 ..... | 0431395 | 13,4 |
| 120x14100 ..... | 0778647 | 13,4 |
| 140x 6050 ..... | 0997387 | 16,0 |
| 140x12100 ..... | 0431411 | 16,0 |
| 140x14100 ..... | 0778704 | 16,0 |
| 160x12100 ..... | 0431429 | 18,8 |
| 160x14100 ..... | 0974089 | 18,8 |
| 180x12100 ..... | 0431437 | 22,0 |
| 180x14100 ..... | 0613596 | 22,0 |
| 200x12100 ..... | 0431445 | 25,3 |
| 200x14100 ..... | 0658120 | 25,3 |
| 220x12100 ..... | 0431452 | 29,4 |
| 220x14100 ..... | 0658138 | 29,4 |
| 240x12100 ..... | 0391433 | 33,2 |
| 240x14100 ..... | 0431460 | 33,2 |
| 260x12100 ..... | 0384420 | 37,9 |
| 260x14100 ..... | 0431478 | 37,9 |
| 280x12100 ..... | 0950345 | 41,8 |
| 300x12100 ..... | 0705160 | 46,2 |
| 300x14100 ..... | 0431494 | 46,2 |
| 320x12100 ..... | 0422337 | 59,5 |
| 400x12100 ..... | 0934950 | 71,8 |

## TĒRAUDA PROFILS


UPE - S 235 JRG2/EN 10025  
(Rst 37-2)  
Sertifikāts 2.2 (3.1.B)/EN 10204  
Tolerance DIN 1026  
Garums 12 metri -0/+100mm



| mm        | Kods    | kg/m |
|-----------|---------|------|
| 80 .....  | 0481010 | 7,9  |
| 100 ..... | 1068113 | 9,8  |
| 120 ..... | 1069996 | 12,1 |
| 140 ..... | 1070101 | 14,5 |
| 160 ..... | 1070184 | 17,0 |
| 180 ..... | 1070192 | 19,7 |
| 200 ..... | 1070200 | 22,8 |

## TĒRAUDA PROFILS

HEA - S 235 JRG2/EN 10025  
(Rst 37-2)  
Sertifikāts 2.2 (3.1.B)/EN 10204  
Tolerance DIN 1025  
Izmērus skat. 69 lpp.




| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 100x12100 ..... | 0667089 | 16,7 |
| 120x12100 ..... | 0667097 | 19,9 |

Turpinājums lpp. 20

| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 140x12100 ..... | 0667105 | 24,7 |
| 160x12100 ..... | 0520528 | 30,4 |
| 180x12100 ..... | 0520585 | 35,5 |
| 200x12100 ..... | 0520718 | 42,3 |
| 220x12100 ..... | 1125996 | 50,5 |
| 240x12100 ..... | 0520833 | 60,3 |
| 300x12100 ..... | 0350918 | 88,3 |

## TĒRAUDA PROFILS


HEB - S 235 JRG2/EN 10025  
(Rst 37-2)  
Sertifikāts 2.2 (3.1B)/EN 10204  
Tolerance DIN 1025  
Izmērus skat. 69 lpp.



| mm              | Kods    | kg/m  |
|-----------------|---------|-------|
| 100x12100 ..... | 0431643 | 20,4  |
| 100x14100 ..... | 0431650 | 20,4  |
| 120x12100 ..... | 0431668 | 26,7  |
| 120x14100 ..... | 0431676 | 26,7  |
| 140x12100 ..... | 0431684 | 33,7  |
| 140x14100 ..... | 0431692 | 33,7  |
| 140x15100 ..... | 0974154 | 33,7  |
| 160x12100 ..... | 0431700 | 42,6  |
| 160x14100 ..... | 0431718 | 42,6  |
| 180x12100 ..... | 0431726 | 51,2  |
| 180x14100 ..... | 0431734 | 51,2  |
| 180x15100 ..... | 0997445 | 51,2  |
| 200x12100 ..... | 0431742 | 61,3  |
| 200x14100 ..... | 0431759 | 61,3  |
| 200x15100 ..... | 0974196 | 61,3  |
| 220x12100 ..... | 0431767 | 71,5  |
| 220x14100 ..... | 0431775 | 71,5  |
| 240x12100 ..... | 0431783 | 83,2  |
| 240x14100 ..... | 0431791 | 83,2  |
| 260x12100 ..... | 0431809 | 93,0  |
| 260x14100 ..... | 0431817 | 93,0  |
| 280x12100 ..... | 1024843 | 103,1 |
| 280x14100 ..... | 0431825 | 103,1 |
| 300x12100 ..... | 0431833 | 117,0 |
| 300x14100 ..... | 0431841 | 117,0 |
| 320x12100 ..... | 0686832 | 126,7 |
| 320x14100 ..... | 0431858 | 126,7 |
| 340x12100 ..... | 0974303 | 134,2 |
| 340x14100 ..... | 1024884 | 134,2 |

## TĒRAUDA PROFILS

IPE - S 235 JRG2/EN 10025  
(Rst 37-2)  
Sertifikāts 2.2 (3.1B)/EN 10204  
Tolerance DIN 1025  
Izmērus skat. 69 lpp.




| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 80x12100 .....  | 0432039 | 6,0  |
| 100x12100 ..... | 0432047 | 8,1  |
| 100x14100 ..... | 0776328 | 8,1  |
| 120x12100 ..... | 0432054 | 10,4 |
| 120x14100 ..... | 1245406 | 10,4 |
| 140x12100 ..... | 0432070 | 12,9 |

| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 140x14100 ..... | 0432088 | 12,9 |
| 140x15100 ..... | 1159086 | 12,9 |
| 160x12100 ..... | 0432096 | 15,8 |
| 160x14100 ..... | 0432104 | 15,8 |
| 160x15100 ..... | 1134386 | 15,8 |
| 180x12100 ..... | 0432112 | 18,8 |
| 180x14100 ..... | 0906339 | 18,8 |
| 180x15100 ..... | 0794859 | 18,8 |
| 200x12100 ..... | 0432138 | 22,4 |
| 200x14100 ..... | 0432146 | 22,4 |
| 200x15100 ..... | 0794867 | 22,4 |
| 220x12100 ..... | 0432153 | 26,2 |
| 220x14100 ..... | 0778589 | 26,2 |
| 220x15100 ..... | 0393819 | 26,2 |
| 240x12100 ..... | 0432179 | 30,7 |
| 240x14100 ..... | 0432187 | 30,7 |
| 240x15100 ..... | 0302117 | 30,7 |
| 270x12100 ..... | 0432195 | 36,1 |
| 270x14100 ..... | 0432203 | 36,1 |
| 270x15100 ..... | 0384909 | 36,1 |
| 300x12100 ..... | 0432229 | 42,2 |
| 300x14100 ..... | 0997395 | 42,2 |
| 300x15100 ..... | 0794891 | 42,2 |
| 330x12100 ..... | 0918839 | 49,1 |
| 330x14100 ..... | 0432245 | 49,1 |
| 330x15100 ..... | 1290501 | 49,1 |
| 360x12100 ..... | 0918847 | 57,1 |
| 360x15100 ..... | 0335182 | 57,1 |
| 400x12100 ..... | 0414185 | 66,3 |
| 400x14100 ..... | 0432260 | 66,3 |
| 400x15100 ..... | 1199587 | 66,3 |
| 450x14100 ..... | 0432278 | 77,6 |
| 450x15100 ..... | 0458893 | 77,6 |
| 500x15100 ..... | 0413039 | 90,7 |

## CINKOTS TĒRAUDA PROFILS


UNP - S 235 JRG2/EN 10025  
(Rst 37-2)  
Tolerance DIN 1026



| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 80x 6000 .....  | 0494120 | 9,3  |
| 100x 6000 ..... | 0494138 | 11,6 |
| 120x 6000 ..... | 0442970 | 13,9 |
| 140x 6000 ..... | 0443028 | 16,6 |

## TĒRAUDA PROFILS

UNP - S 355 J2G3/EN 10025  
(St 52-3 N)  
Sertifikāts 3.1.B/EN 10204  
Tolerance DIN 1026




| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 160x 6050 ..... | 0325233 | 18,8 |
| 160x12100 ..... | 1163112 | 18,8 |
| 200x 6050 ..... | 0325241 | 25,3 |
| 200x12100 ..... | 1163120 | 25,3 |

| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 240x 6050 ..... | 0325340 | 33,2 |
| 240x12100 ..... | 1163146 | 33,2 |
| 300x 6050 ..... | 0325357 | 46,2 |
| 300x12100 ..... | 1163153 | 46,2 |

## TĒRAUDA PROFILS


HEB - S 355 J2G3/EN 10025  
(St 52-3 N)  
Sertifikāts 3.1.B/EN 10204  
Tolerance DIN 1025



| mm              | Kods    | kg/m  |
|-----------------|---------|-------|
| 160x 6050 ..... | 0325043 | 42,6  |
| 160x12100 ..... | 1162205 | 42,6  |
| 180x 6050 ..... | 1187624 | 51,2  |
| 180x12100 ..... | 1177062 | 51,2  |
| 200x 6050 ..... | 0325050 | 61,3  |
| 200x12100 ..... | 1162924 | 61,3  |
| 240x 6050 ..... | 0325068 | 83,2  |
| 240x12100 ..... | 1162999 | 83,2  |
| 300x 6050 ..... | 0325084 | 117,0 |
| 300x12100 ..... | 1163013 | 117,0 |
| 400x 6050 ..... | 1187632 | 155,3 |
| 400x12100 ..... | 1163039 | 155,3 |

## TĒRAUDA PROFILS

IPE - S 355 J2G3/EN 10025  
(St 52-3 N)  
Sertifikāts 3.1.B/EN 10204  
Tolerance DIN 1025



| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 160x 6050 ..... | 735704  | 15,8 |
| 160x12100 ..... | 1163047 | 15,8 |
| 180x 6050 ..... | 1187574 | 18,8 |
| 200x 6050 ..... | 0325126 | 22,4 |
| 200x12100 ..... | 1163054 | 22,4 |
| 240x 6050 ..... | 0325159 | 30,7 |
| 240x12100 ..... | 1163070 | 30,7 |
| 300x 6050 ..... | 0325167 | 42,2 |
| 300x12100 ..... | 1163088 | 42,2 |
| 400x 6050 ..... | 1187640 | 66,3 |
| 400x12100 ..... | 1163104 | 66,3 |


## PALIKTŅU PLĀKSNE

S235 JRG2

| mm               | Kods    | kg/gab. |
|------------------|---------|---------|
| 100x100x10 ..... | 0787721 | 0,80    |
| 150x150x10 ..... | 0787770 | 1,80    |
| 200x200x10 ..... | 0787820 | 3,20    |
| 250x250x10 ..... | 0787861 | 5,00    |

## STIEGROJUMA APALTĒRAUDS


R St 37-2/DIN 17100  
Tolerance DIN 488



| mm              | Kods    | kg/m |
|-----------------|---------|------|
| 5,5x8000 .....  | 1008887 | 0,19 |
| 7x 8000 .....   | 0658864 | 0,30 |
| 8x 12000 .....  | 0430603 | 0,40 |
| 10x 12000 ..... | 0430611 | 0,62 |
| 12x 12000 ..... | 0430629 | 0,89 |
| 14x 12000 ..... | 0430645 | 1,21 |
| 16x 12000 ..... | 0777235 | 1,58 |

## STIEGROJUMA APALTĒRAUDS


DOBBĒLTBEROLIGET  
Kvalitāte RR St 44-3  
Garums 12 metri  
(Sertifikāts 3.1B/EN 10204)



| mm             | Kods    | kg/m |
|----------------|---------|------|
| 10x12000 ..... | 1161512 | 0,62 |
| 12x 8000 ..... | 0314682 | 0,89 |
| 14x12000 ..... | 1161538 | 1,21 |
| 16x12000 ..... | 1161546 | 1,58 |

## STIEGROJUMA APALTĒRAUDS

BST 500 S (IV S)  
Tolerance DIN 488



| mm             | Kods    | kg/m |
|----------------|---------|------|
| 6x12000 .....  | 0945816 | 0,23 |
| 8x12000 .....  | 0945824 | 0,40 |
| 10x 6000 ..... | 1080746 | 0,62 |
| 10x12000 ..... | 0951491 | 0,62 |
| 12x 6000 ..... | 0348672 | 0,89 |
| 12x12000 ..... | 0945832 | 0,89 |
| 14x12000 ..... | 1157874 | 1,21 |
| 16x12000 ..... | 0959932 | 1,58 |
| 20x12000 ..... | 1120369 | 2,48 |
| 25x12000 ..... | 0909226 | 3,85 |